

FF Wax

Microcement floor maintenance wax for indoor use.

PRODUCT DESCRIPTION



FF Wax is a product based on waxes and acrylics, which, when applied, creates a waterproof, protective and maintenance coating. The coating is hard, abrasion-resistant and has an anti-slippery effect. The product is intended for varnished surfaces, including microcement floors. It works very well as an additional coating protection. It can be successfully used as a sealer restorer. The product is odorless, vapor-permeable, resistant to polishing and alcohol disinfection.

APPLICATION



Before applying the product, the surface must be dry (less than 3% humidity) and thoroughly dusted and washed. Shake the container with the **FF Wax** well. The product is ready-to-use, it should not be diluted. Apply in sections, using a microfiber mop in 2-3 thin layers. The drying time between coats is at least 60 minutes. Additional polishing, increasing the gloss, can be done with a soft pad after the surface is completely dry (2-3 days).

Do not use outdoors - the product is sensitive to low temperatures.

TECHNICAL DATA

- Color: milky
- pH: 8.0-9.0
- Shelf life: 24 months in unopened original packaging (store above 15 ° C, protect against frost and direct sunlight)
- Consumption: consumption of the product depends on the surface and method of application, and for one layer it is approx. 1-3 l per 100 m²
- Application temperature: + 15 ° C ÷ + 25 ° C
- Gloss level: available in both satin and gloss



SAFETY AND HEALTH



Observe the general health and safety rules and other rules contained in the safety data sheet. The product is a non-hazardous substance, is not hazardous during transport, has not been classified in any toxicity class, and does not require special precautions for storage.

The product is a mixture of the highest quality ingredients, mainly: waxes, acrylics, surfactants, solvents and preservatives.

PACKAGING



FF Wax is available in packages of 1 l.